

**Peter Kiewit Sons ULC**  
**Kiewit WCD Marine Yard**  
**Build-Out Project**  
**1950 Brigantine Drive, Coquitlam, BC**  
**VFPA PER No. 23-130**

***STORMWATER POLLUTION PREVENTION PLAN (SPPP)***

Revision	Date	Remarks
A	April 11, 2024	Issued for Review
B	October 20, 2024	Issued for Review

**Prepared by:**



**Peter Kiewit Sons ULC**

## TABLE OF CONTENTS

List of Figures .....	ii
List of Appendices .....	iii
<b>1 INTRODUCTION .....</b>	<b>1</b>
<b>2 Project Description .....</b>	<b>1</b>
2.1 Location.....	1
2.2 Current Use .....	2
2.3 Project Scope .....	2
2.3.1 First Phase.....	2
2.3.2 Second Phase .....	2
2.4 Activities .....	3
2.4.1 Construction.....	3
2.4.2 Operations .....	3
2.5 Potential Pollutant Sources .....	4
2.6 Hydrologic Assessment.....	4
2.6.1 Drainage Design Criteria .....	5
2.6.2 Existing Site Drainage System .....	5
2.6.3 Proposed New Site Drainage System .....	7
<b>3 ISSUES IDENTIFICATION AND RISK ANALYSIS .....</b>	<b>8</b>
3.1 Applicable Standards, Acts and Regulations .....	8
3.2 Potential Sensitive Receptors .....	9
3.3 Identified Issues .....	9
3.4 Identified Pollutant Pathways.....	9
<b>4 STORMWATER POLLUTION PREVENTION PLAN .....</b>	<b>10</b>
4.1 Management Strategy .....	10
4.1.1 Good Housekeeping .....	10
4.1.2 Preventive Maintenance .....	10
4.1.3 Inspections.....	10
4.1.4 Containment/Reduction .....	11
4.1.5 Spill Prevention and Response Procedures .....	11
4.1.6 Treatment.....	11
<b>5 IMPLEMENTATION AND MONITORING .....</b>	<b>11</b>
5.1 Inspections .....	11
5.2 Water Quality Monitoring.....	12
5.3 Adaptive Management and Continuous Improvement.....	13

## List of Figures

Figure 1:	Project Location .....	1
Figure 2:	Proposed Project Upgrades.....	3

## List of Appendices

Appendix A Marine Yard Stormwater Design Drawings



## 1 INTRODUCTION

This Stormwater Pollution Prevention Plan (SPPP) is developed for the construction of the Peter Kiewit Sons ULC (Kiewit) Marine Yard Build-Out Project (the Project) and the operation of the Marine Yard (the Yard).

The purpose of the SPPP is to develop a pollutant control strategy to minimize the discharge of pollutants by stormwater runoff. Best Management Practices (BMPs) are those management practices which are considered sound, are relatively low in cost, and are applicable to a broad category of industries and types of pollutants. Advanced BMPs are defined as those which are specific to a type of industry or pollutant. The BMPs discussed in this plan have been designed to improve the quality of stormwater discharged from the facility and to aid in the development and implementation of the SPPP.

## 2 PROJECT DESCRIPTION

### 2.1 Location

As shown in Figure 1, the Project is located at the Vancouver Fraser Port Authority (VFPA) water lot lease at 1950 Brigantine Drive, Coquitlam, BC on the north side of the main arm of the Fraser River at the eastern end of Sapperton Channel approximately 2.2 km downstream of the Port Mann Bridge. At the Project location, the Fraser River is considered freshwater as the upper boundary of the Fraser River salt wedge is at the downstream end of Sapperton Channel.



Figure 1: Project Location

## 2.2 Current Use

At present, the property is used to service Kiewit's marine fleet and other construction equipment. Yard operations generally consist of staging equipment and materials on land, transferring materials to/from barges and fabrication of materials required for our projects. A Disposal At Sea (DAS) operation is also conducted from the facility. The Marine Yard has several structures and fixed facilities that were installed by the previous owner, including an office building, truck weigh scale, boat ramp, and two marine bulkhead wall structures.

## 2.3 Project Scope

Kiewit is planning to build-out the Marine Yard to ensure it meets modern environmental and engineering standards. The following is a summary of the proposed project upgrades and are also shown in Figure 2.

### 2.3.1 First Phase

- Dredging in the intertidal area to a depth of approximately -6.5 chart datum (CD) for safe operation of marine construction equipment, including barges and support vessels; and,
- Removal and relocation of existing piles to accommodate marine equipment (barges).

### 2.3.2 Second Phase

- Infilling and yard widening between the proposed access trestle and DAS loading platform (outlined in bold green and pink in the site plan, below), approximately 3,600 square metres;
- Creation of three barge mooring zones by installing steel pipe pile mooring dolphins;
- Installation of a marine access trestle for barge loading and unloading;
- Installation of a DAS loading platform approximately 1,122 square metres and conveyor system;
- Uplands works:
  - Electrical and lighting upgrades;
  - Grading;
  - Drainage and new stormwater infrastructure to accommodate the infilled area;
  - Domestic water supply connection;
  - Installation of a truck scale;
  - Installation of a truck wheel wash; and,
- Creation of onsite habitat offsetting – approximately 7,745 square metres of intertidal marsh bench (Fisheries Act Authorization offsetting area).

### Figure 2: Proposed Project Upgrades

## 2.4 Activities

The following activities are expected to occur during both the construction of the Project and operation of the Yard.

### 2.4.1 Construction

- Excavation, infill, grading and paving;
- Demolition of existing structures;
- Fueling, maintenance and washing of construction equipment;
- Cast-in-place concrete work;
- Aggregate storage;
- Material preparation (e.g., cutting, welding, cleaning, painting);
- soil and water sampling;
- waste handling, storage and disposal; and,
- soil and water sampling.

## 2.4.2 Operations

- Aggregate storage and handling;

- Barge loading;
- Barge maintenance;
- Fueling, maintenance and washing of equipment;
- Equipment and small truck storage;
- Material preparation (e.g., cutting, welding, cleaning, painting); and
- waste handling, storage and disposal.

## **2.5 Potential Pollutant Sources**

An assessment of the Marine Yard was conducted to identify materials and practices which may reasonably be expected to add significant levels of pollutants to stormwater or which may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Potential sources which may contribute to the presence of contaminants in stormwater runoff are listed below.

- Metals;
- Aggregates;
- Uncured concrete;
- Asphalt paving;
- Washwater;
- Fuels, oils and other hydrocarbons;
- Paints and solvents;
- Cleaning products;
- Antifreeze;
- Solid waste;
- Sanitary waste from blueboys;
- Hazardous waste;
- Contaminated soils; and,
- Dewatering water.

## **2.6 Hydrologic Assessment**

A hydrologic assessment was conducted for the final design of the site to estimate the runoff response, including peak flow rates and runoff volumes for various rainfall events. The design of the site stormwater management system will take into account the results of the hydrological assessment to ensure the stormwater infrastructure is appropriate for the site.

### 2.6.1 Drainage Design Criteria

The following criteria and assumptions were considered for the design of the Yard drainage system.

- Rational Method used to estimate the design flows;
- Model used rainfall data from the City of Coquitlam Zone 3 rainfall station;
- The 2021 Intensity-Duration-Frequency (IDF) curve was used to evaluate the capacity of the existing infrastructure;
- The 2050 IDF curve was used to evaluate the capacity of the new drainage infrastructure;
- The catch basins and piping systems were designed to accommodate 10-year storm event flows;
- Personal Computer Storm Water Management Model (PCSWMM) software was used to analyze the peak flow for the water quality volume design with the following assumptions:
  - The 24-hour rainwater depth for 2050 is 96mm;
  - The water quality design volume for the sediment control chambers was designed to treat the runoff volume resulting from the 24-hour storm with a 6-month return period. The 6-month 24-hour storm was estimated as 70% of the 2-year 24-hour storm; and,
  - The equation for calculation of the sediment chamber surface area is  $A=Q/V_s$ , where:

$A$  = Surface area of the sediment chamber (m<sup>2</sup>);

$Q$  = Flow rate (m<sup>3</sup>/s);

$V_s$  = Sediment setting velocity (m/s) and,

Coarse silt is assumed to be the sediment particles for the site, the setting velocity is 0.0026 m/s.

### Modeling Results

	Peak Flow (m <sup>3</sup> /s)	Catchment Area (m <sup>2</sup> )
To Sediment Chamber	0.038	6160

**Table 1. Modeling Result the 2-Year, 24-hour storm event.**

The peak flow for the 6-month rainfall event is  $0.039 \times 70\% = 0.0266$  (m<sup>3</sup>/s) and the required surface area for the sediment chamber will be 10.2m<sup>2</sup>.

### 2.6.2 Existing Site Drainage System

The majority of the site is graded with a slope that runs transversely from the south to the north, and longitudinally from the west to the east.



The existing yard drainage system is composed of two separate sediment control facilities each connected to a single catch basin. The existing drainage system was installed by the previous property owner at an unknown date. The existing drainage system collects and treats the storm water runoff from the west and east portions of site before getting discharged to the Fraser River.

The runoff from the west portion of the site drains to a swale located along the north property line at the bottom of the City of Coquitlam greenway slope along the back of the property. At the end of the swale, a lawn basin was installed to collect the runoff and direct it to the west sediment control facility via a culvert that passes directly under the yard. The treated water overflows from the sediment control facility and is directed towards its discharge point into the Fraser River.

The catchment areas for the west sediment control facility are as follows:


- City of Coquitlam property: 5489 m<sup>2</sup>
- Freehold property: 3456 m<sup>2</sup>
- VFPA leased land: 3456 m<sup>2</sup>

The runoff from the eastern section of the site is collected through swales and catch basins and directed towards the east sediment control facility via a culvert. The existing east section system contains an oil-water separator which is located between the existing maintenance shop and the future maintenance shop. The treated water overflows from the sediment control facility and is directed towards its discharge point into the Fraser River.

The catchment areas for the western sediment control facility are as follows:

- Freehold property: 21067 m<sup>2</sup>
- VFPA leased land: 805 m<sup>2</sup>

Key existing drainage features are identified in Figure 3.



**Figure 3: Existing Drainage Features**

Development of the site will involve a localized expansion of the yard's finished grade at both the Bottleneck area, and the area located directly to the east (between the bottleneck area and the existing boat ramp). While a new stormwater drainage system is proposed for the expanded catchment area, drainage design recommends maintaining the existing system for the original catchment areas as follows:

#### **West Drainage area**

- Maintain the existing swale located within the City of Coquitlam (CoC) Right-of-Way ensuring compliance with the CoC drainage regulations and guidelines;
- Implement measures prevent erosion and stabilize exposed bare soils (e.g., installation of erosion control blankets, riprap, hydroseeding, etc.);
- Regularly inspect and maintain the erosion control socks to prevent sediment from entering the lawn basin; and,
- Relocate the existing sediment trap of similar size to a suitable location, post construction.

#### **East Drainage area**

As there is currently no yard development scope that will impact the existing east drainage area facilities, no modifications to the existing system are required. Inspection and maintenance for the existing east drainage facilities should continue to prolong service life.

### **2.6.3 Proposed New Site Drainage System**

As part of the overall development, a plan has been formulated to infill the bottleneck area and expand the yard width to the south for a section with a linear distance of approximately 120 meters parallel to the shoreline in the eastward direction (see Figure 3). This extension aims to create more space to accommodate dump truck traffic at the bottleneck area and widen the existing yard capacity from 6 to 12 meters. The infilling and yard expansion process will result in a new catchment area of approximately 4,240 m<sup>2</sup> with an asphalt pavement top finish.

The expansion will add additional stormwater runoff that will need to be managed by a new drainage system. Construction of a new drainage system is recommended over modification of the existing system due to uncertainty with the existing system and to avoid upgrading the complete existing system to current standards. This strategy also avoids the need for a comprehensive hydrological and hydraulic analysis of the existing drainage system. The proposed new drainage system will include the following components:

#### **Outfalls:**

The new drainage design will include three new outfalls and the extension of existing outfall. The outfalls are numbered 1 through 4 on drawing DWG-4101 provided in Appendix A. Design information for the four outfalls is as follows:

- **Outfall 1:** This outfall serves the new timber surface run-on-off, with a total catchment area of 278 m<sup>2</sup>. The 10-year discharge rate is 0.0045 m<sup>3</sup>/s.
- **Outfall 2:** This outfall involves the relocation of the existing silt control chamber. The sediment control facility was reconstructed in Spring 2023 using precast concrete lock

blocks, with internal dimensions of 6.70 m (length) x 2.13 m (width) and a sump depth of approximately 0.35 m. Due to yard expansion, the existing sediment trap will be removed and replaced with a new silt control chamber upstream of Outfall 2.

- **Outfall 3:** This outfall is an extension of an existing 600 mm outfall, which discharges groundwater from the City of Coquitlam. No record information is available for this discharge.
- **Outfall 4:** A new drainage system, including a silt control chamber, will collect runoff from an additional 4,240 m<sup>2</sup> from the yard expansion and 1,376 m<sup>2</sup> from the new timber surface trestle. The total discharge rate for a 10-year storm event is 0.071 m<sup>3</sup>/s.

#### **Sump Manhole with Grate Lid:**

Along the infilled areas, sump manholes with grate lids will be constructed. These manholes will collect and convey stormwater runoff from the infilled area, facilitating effective drainage.

#### **Sediment Control Chamber:**

To enhance sedimentation treatment, a sediment control chamber will be installed. This chamber will help capture and retain sediment, preventing it from entering the Fraser River. By implementing the proposed separate drainage system for the infilled area, we can effectively manage the increased stormwater runoff and mitigate potential sedimentation issues. The combination of a riprap lined swale, a sediment control chamber will contribute to the overall sustainability and environmental compliance of the project.

Design drawings showing the details of the proposed new drainage system details is provided in Appendix A.

### **3 ISSUES IDENTIFICATION AND RISK ANALYSIS**

#### **3.1 Applicable Standards, Acts and Regulations**

The following relevant legislation and standards are applicable given the potential pollutant sources listed above.

- Canada *Fisheries Act* regarding the deposition of deleterious substance in waters frequented by fish;
- Canada *Shipping Act*, National Spill Response Protocol regarding the release of pollutants to the marine environment;
- Canada *Environmental Protection Act* regarding the management of harmful substances;
- Canada *Transportation of Dangerous Goods Act* – regarding the transportation of dangerous goods;
- Canadian Council of Ministers of the Environment (CCME) Guidelines relating to water quality standards;
- B.C. *Environmental Management Act*, regarding the unauthorized release of substances into the environment;
- B.C. *Environmental Management Act*, regarding the storage, handling, and disposal of hazardous materials and waste;
- Master Municipal Construction Documents, MMCD, Platinum Edition;
- Metro Vancouver Stormwater Design Guidelines; and,
- City of Coquitlam Stormwater Management Policy and Design Manual.



### 3.2 Potential Sensitive Receptors

According to the *Vancouver Fraser Port Authority Land Use Plan* (December 8, 2020), the Marine Yard is located in Planning Area 5, Fraser River Central and designated as 'Industrial' land use. The Marine Yard is located at the Vancouver Fraser Port Authority (VFPA) water lot lease at 1950 Brigantine Drive, Coquitlam, BC on the north side of the main arm of the Fraser River at the eastern end of Sapperton Channel approximately 2.2 km downstream of the Port Mann Bridge.

Directly west of the Marine Yard lies Don Roberts Park and Como Creek. To the east lies the Fraser River Greenway Park with trail access from the alleyway at 1950 Brigantine Drive. While there are no residential areas within 500 meters of the Yard site currently, a future residential development of Fraser Mills is planned west of Como Creek.

Como Creek has been identified as critical habitat for the western painted turtle (*Chrysemys picta bellii*), Pacific Coast population which is a species listed on Schedule 1 of the *Species at Risk Act* (SARA). Subsection 58(1) of SARA contains prohibitions against destroying any part of critical habitat for at-risk species on federal land, including the VFPA lease area. An application for a SARA permit has been submitted to ECCC for the portion of the Marine Yard VFPA lease area that overlaps with western painted turtle critical habitat.

The stormwater design for the Yard has all stormwater runoff directed through four outfall pipes into the Fraser River. The implementation of this SPPP, associated mitigation measures and stormwater design will minimize harmful impacts from stormwater runoff to Fraser River.

### 3.3 Identified Issues

Given that grain and grain dust recovery systems will be in place during terminal operation, the risk of the release of these potential pollutants into stormwater is considered to be low.

There will be no large tank-type bulk fuel storage during the operational phase of the project. The storage area for small amounts of fuels, coolants hydraulic oils and lubricating oils used for maintenance purposes will be in a centralized location having secondary containment. Given that the potential source for the release of these pollutants into the environment will be primarily during maintenance operations (either planned or from equipment failure), operations crews conducting the maintenance will immediately clean up and report all spills in accordance with the site Spill Prevention and Emergency Response Plan. The risk for the introduction of chemical pollutants will be low with an effective implementation of the Spill Prevention and Emergency Response Plan.

### 3.4 Identified Pollutant Pathways

The only pollutant pathway for the site will be via the stormwater drainage system. The entire site will be graded so that all rainfall and snow melt is directed into a network of catch basins and sub-grade culverts to the outfalls.

A detailed site drainage plan drawings provided in Appendix A include the details on the two oil-water-grit interceptors (commercial name 'Stormceptor') and two sediment chambers. The site drainage drawing includes the following features:

- The direction of flow through the stormwater system;
- Catchment area boundaries;

- Stormwater drainage infrastructure;
- Stormwater drainage collection points;
- Stormwater drainage release points from the site;
- Location of treatment and retention units; and,
- Receiving water bodies.

## **4 STORMWATER POLLUTION PREVENTION PLAN**

### **4.1 Management Strategy**

The Marine Yard stormwater pollution prevention strategy is to implement a set of best management practices to target the potential pollutant sources identified in section 4.2 of this plan. These practices will encompass prevention, containment, reduction and treatment.

#### **4.1.1 Good Housekeeping**

Maintenance of work areas which may contribute pollutants to stormwater will be the most effective management practice for this site. Good housekeeping practices are not only beneficial in terms of limiting exposure of materials to stormwater, but they also improve worker safety and often contribute to reducing losses of products thereby lowering operational or capital costs.

Good housekeeping will be practiced throughout the facility. All exposed areas of the facility are maintained in a clean and orderly manner. Trash and other waste products are removed from the site on a regular basis. Routine inspections are made to ensure that good housekeeping is being practiced.

#### **4.1.2 Preventive Maintenance**

The Marine Yard will employ a preventive maintenance program that includes inspections, testing, maintenance, and repairs of facility equipment and systems whose failure could result in a non-stormwater discharge is in place at the facility.

#### **4.1.3 Inspections**

A regular inspection schedule will be developed and implemented for the key areas of the stormwater system including but not limited to:

- Catch basin inlets;
- Interceptor ditches;
- Oil-water-grit separators; and,
- Sediment chambers.

The frequency of inspection will be at least monthly and after heavy rainfall events.

#### **4.1.4 Containment/Reduction**

All hazardous material storage areas will be equipped with secondary containment to reduce the likelihood of stormwater to become contaminated by their contents. If the secondary containment accumulates stormwater, the water will be examined to ensure it is free of oil, foam or discoloration prior to being drained.

In areas where there is a likelihood of solid contaminants entering a wastewater drain, the drain will be equipped with a screen to reduce the amount of solids allowed to enter the storm drain.

#### **4.1.5 Spill Prevention and Response Procedures**

Spill prevention and emergency response procedures are outlined in the Spill Prevention and Emergency Response Plan found in the Project Construction Environmental Management Plan (CEMP).

#### **4.1.6 Treatment**

Prior to leaving the property, the stormwater effluent will pass through one of two Stormceptor oil-water-grit (OWG) interceptors. The OWG interceptors are designed to remove sediment, total suspended solids, hydrocarbons and free oil from stormwater runoff. The model is appropriately sized for the predicted storm events for the site. The OWG interceptors will further reduce the chance of discharging any sediment and oily contamination in the stormwater discharge. The OWG interceptors will be inspected and cleaned, as required.

## **5 IMPLEMENTATION AND MONITORING**

### **5.1 Inspections**

Marine Yard Management will identify an operational SPPP Manager who will be responsible for the implementation of this plan. The SPPP Manager will possess the knowledge and skills to assess conditions and activities that could impact stormwater quality at the facility, and who can also evaluate the effectiveness of the management practices.

Regular site and effluent inspections shall be conducted by the SPPP Manager to confirm that stormwater best management practices (BMPs) outlined in this plan are being implemented effectively and to identify any possible concerns related to the quality of stormwater effluent.

At a minimum, the SPPP Manager will conduct weekly inspections of all areas of the facility where industrial materials or activities are exposed to stormwater and/or where the potential for exposure to stormwater exists. Such areas specifically include aggregate receiving areas, aggregate storage areas, aggregate loading areas, the areas around fuel and hazardous storage, the areas where vehicle or equipment maintenance takes place, and waste disposal areas.

In addition to the weekly inspections, the SPPP Manager will monitor local weather reports for upcoming storm events and conduct inspections during a period when a stormwater discharge is occurring. The effluent will be inspected for the presence of odor, foam, discoloration, sediment and/or an oily sheen. If stormwater effluent is found to be abnormal, the cause of the abnormality

will be investigated, and appropriate mitigating action will be taken to return the quality of the stormwater effluent to normal and prevent future reoccurrences.

All SPPP inspections will be documented in an SPPP inspection form that will include weather, BMPs inspected, effluent inspected, effectiveness of the BMPs, any repairs/maintenance of existing BMPs, any new BMPs proposed, the personnel responsible in BMP maintenance or installation and a timeline for completion of the prescribed maintenance or installation.

All operational site staff will receive training on the contents of this plan at hire orientation and annually. The training will clearly indicate that it is the responsibility of all staff to be able to recognize ineffective stormwater BMPs and to report them to their supervisor, the SPPP Manager and/or site management.

Marine Yard Management and the SPPP Manager will review the contents of this plan annually to ensure all potential stormwater exposures have been identified and that the management practices are appropriate and adequate. The plan will be updated to reflect any changes deemed necessary because of this annual review. Inspection reports, monitoring data and stormwater management plan updates will be made available to the port authority upon request.

## 5.2 Water Quality Monitoring

Water discharged from the site will be monitored to confirm that turbidity, total suspended solids and pH levels meet the BC Approved Water Quality Guidelines as outlined in Table 2. Table 2 provides specific criteria for monitoring these parameters to ensure compliance with environmental protection standards. Water quality monitoring sampling locations will be at the current outfalls during construction and then at the four new outfalls once construction is complete.

Parameter	Criteria
Nephelometric Turbidity Units (NTU) <sup>1</sup>	<p><b>Clear Waters (During Clear Flows or in Clear Waters):</b></p> <ul style="list-style-type: none"> <li>Change from background of 8 NTU at any one time for a duration of 24 hours.</li> <li>Change from background of 2 NTU at any one time for a duration of 30 days.</li> </ul> <p><b>Turbid Waters (During High Flows or in Turbid Waters):</b></p> <ul style="list-style-type: none"> <li>Change from background of 5 NTU at any time when background is 8 to 50 NTU.</li> <li>Change from background of 10% when background is &gt;50 NTU at any time.</li> </ul>
Oil and Grease <sup>2</sup>	Not detectable by sight or odour.
pH <sup>1</sup>	6.5-9.0

<sup>1</sup>Values are from B.C. Approved Water Quality Guidelines (Criteria).

<sup>2</sup>Criteria from for Canadian Recreational Water Quality: Physical, Aesthetic and Chemical Characteristics, 2021.

**Table 2 Water Quality Guidelines: Turbidity, Oil & Grease, and pH Standards**

### **5.3 Adaptive Management and Continuous Improvement**

A key process in the effective implementation of the SPPP is the ability to change mitigation measures or actions as site conditions warrant to protect stormwater quality. This approach, generally termed as 'adaptive management', is a planned and systematic process for continuously improving environmental management practices by learning about their outcomes.


On a bi-annual basis, the SPPP Manager along with site management will review the SPPP effectiveness by reviewing the SPPP inspection reports for trends in effective and ineffective mitigation actions and measures. The results of these reviews may determine that current BMPs are working effectively, or additional mitigation efforts are needed. Any changes to the actual SPPP will also be in the review. The reviews will be minuted with clear action items, those responsible and timelines for completion.


# Appendix A

## Marine Yard Stormwater System Design Drawings



DATE: 2024/03/21 - 2:14pm  
PATH: C:\Users\ShunP.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design\_Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4101.dwg





																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
--	--	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--




TITLE BLOCK DL-TB.dwg


DATE: 2024/03/21 - 1:28pm  
PATH: C:\Users\ShunP.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4102.dwg




**SEDIMENT CHAMBER DETAILS**



**OUTFALL DETAILS**



**CATCH BASIN MANHOLE DETAILS**





**STORMCEPTOR DETAILS**

**NOTES:**




- ALL HARDWARE SUCH AS NUTS, BOLTS, TIE RODS, ETC. ARE TO BE 316 STAINLESS STEEL. COAT ALL MECHANICAL HARDWARE WITH PRIMER AND PETROLATUM TAPE TO AWWA C217.

**PRELIMINARY**  
**NOT FOR CONSTRUCTION**  
2024-MAR-01

VFPA DRAWING NUMBER:  
**332-004-UT-###**

							E	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.		DESIGN BY	B.Y.	WCD MARINE YARD BUILD-OUT COQUITLAM, BC STORM DETAILS						
			D	2024-MAR-01	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.	DRAWN BY	T.W.												
			C	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.	APPROVED	K.B.												
			B	2023-SEP-27	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.	DATE	2024-MAR-29												
			A	2023-AUG-23	ISSUED FOR 50%	T.W.	B.Y.	SCALE	1:30												
Ref. No.	REFERENCE						No.	Date	REVISION	Dr'n	Ch'd	ENGINEERING DEPARTMENT	VFPA SITE	332-004	SIZE	DWG.	105716-S00-KIE-DAU-DWG-4102	SHEET	1 OF 1	REV.	E





- ## WATERMAIN NOTES:
1. CONSTRUCTION WORKS SHALL CONFORM TO THE MASTER MUNICIPAL CONSTRUCTION DOCUMENT AND STANDARD DETAIL DRAWINGS (MMCD), PLATINUM EDITION (2019) SECTION 33 11 01 WATERWORKS.
  2. MINIMUM 1.0m COVER FOR ALL WATERWORKS.
  3. MINIMUM OF 1.0m HORIZONTAL CLEARANCE AND 300mm CLEAR VERTICAL SEPARATION BETWEEN WATERMAINS AND ELECTRICAL/ COMMUNICATION CONDUITS EXCEPT WHERE NOTED.
  4. DISINFECTION AND FLUSHING PROCEDURES SHALL BE IN ACCORDANCE WITH MMCD SECTION 33 11 01, 3.21.
  5. THE CONTRACTOR SHALL CONFIRM LOCATION AND ELEVATION OF EXISTING UTILITIES AT ALL CROSSINGS AND CONNECTIONS PRIOR TO CONSTRUCTION
  6. ALL 50mm WATERLINES MATERIAL TO BE UPONOR PEX WHITE OR EQUIVALENT.
  7. ALL PEX FITTINGS SHALL BE ProPEX ENGINEERED POLYMER (EP) TO ASTM F2023 AND IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. ( OR EQUIVALENT )
  8. ALL PEX JOINTS SHALL BE ProPEX RINGS AND ProPEX TOOL IS REQUIRED. ( OR EQUIVALENT )
  9. ALL PEX JOINTS SHALL BE WRAPPED WITH DENSO PETROLATUM TAPE.


PRELIMINARY  
NOT FOR CONSTRUCTION  
2023-SEP-27

VFPA DRAWING NUMBER  
**332-004-UT-4003**

[illegible]



DATE: 2024/03/18 - 3:35pm  
PATH: C:\Users\ShunP.Wang\OneDrive\PC\ACCDocs\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4104.dwg



LEGEND

EXISTING DITCH

EXISTING STORM

PROPOSED STORM

CATCHMENT AREA

EXISTING OVERLAND FLOW

PROPOSED OVERLAND FLOW

INFORMATION ONLY

Ref. No.	REFERENCE



C	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.	
B	2024-MAR-01	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.	
A	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.	
No.	Date	REVISION	Dr'n	Ch'd	

PORT of  
vancouver

Vancouver Fraser  
Port Authority

ENGINEERING DEPARTMENT

DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	1:600
VFPA SITE	332-004

WCD MARINE YARD BUILD-OUT  
COQUITLAM, BC  
STORMWATER MANAGEMENT PLAN

SIZE DWG

105716-S00-KIE-DAU-DWG-4104

SHEET

1 OF 1



REV.

C


VFPA DRAWING NUMBER:  
332-004-UT-###





DATE: 2024/03/18 - 3:51 pm  
PATH: C:\Users\ShunP.Wang\OneDrive\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4105.dwg



ALIGNMENT: MY STM 1

STORM TYPE, SIZE LENGTH AND GRADE		PROP 22.12m OF 450mmØ C76 CLASS IV CONC @ 0.5%				
STORM SEWER INVERT ELEVATIONS		4.43 (S) 4.43 (W)	4.32 (N)	4.32 (S)	4.31 (N) 4.28 (S)	4.16 (N)
GROUND ELEVATION	10.06		5.70		6.08 6.12	1.55
CHAINAGE	11+000	11+013.84 11+025	11+035.96 11+048.23 11+042.29	11+050	11+066.82	11+075 11+090



ALIGNMENT: MY STM 4

STORM TYPE, SIZE LENGTH AND GRADE			PROP 31.68m OF 600mmØ C76 CLASS III CONC @ 0.5%			
STORM SEWER INVERT ELEVATIONS			3.01 (N) 3.01 (S)			2.85 (N)
GROUND ELEVATION		5.84 5.74	1.99 5.98		1.65	
CHAINAGE	14+050.83		14+035	14+003.32		

PRELIMINARY  
NOT FOR CONSTRUCTION  
2024-MAR-01

VFPA DRAWING NUMBER:  
332-004-UT-###






DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	H 1:500 V: 1:50
VFPA SITE	332-004

WCD MARINE YARD BUILD-OUT  
COQUITLAM, BC  
STORM PLAN AND PROFILE  
SHEET 1 OF 3

Ref. No.	REFERENCE	No.	Date	REVISION	Dr'n	Ch'd	ENGINEERING DEPARTMENT	SIZE	DWG.	105716-S00-KIE-DAU-DWG-4105	SHEET	1 OF 3	REV.	C
----------	-----------	-----	------	----------	------	------	------------------------	------	------	-----------------------------	-------	--------	------	---







STORM TYPE, SIZE LENGTH AND GRADE							
STORM SEWER INVERT ELEVATIONS			4.40 (S)		4.39 (N)	4.36 (S)	4.30 (N)
GROUND ELEVATION		5.94	5.94				2.00
CHAINAGE			15+015.54		15+001.27		

VFPA DRAWING NUMBER  
**332-004-UT-###**



DATE: 2024/03/21 - 2:03pm  
PATH: C:\Users\ShunP.Wang\OneDrive\CV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4107.dwg



STORM TYPE, SIZE LENGTH AND GRADE		PROP. 8.98m OF 375mmØ C76 CL III PVC @ 0.5%	PROP. 32.83m OF 375mmØ C76 CL III PVC @ 0.5%	PROP. 26.87m OF 375mmØ C76 CL III CONC @ 0.5%	PROP. 25.96m OF 375mmØ C76 CL III CONC @ 0.5%	
STORM SEWER INVERT ELEVATIONS		4.40 (SE) 4.44 (NW) 4.44 (E) 4.82 (NE)	4.61 (W) 4.61 (E)	4.74 (W) 4.74 (E)	4.86 (W) 4.94 (S)	
GROUND ELEVATION		5.93 6.06	5.92 6.07	5.93 5.99	5.93 6.03	5.97 6.03
CHAINAGE	12+975	13+000 13+001.24	13+010.22	13+025	13+043.05	13+050

PRELIMINARY  
NOT FOR CONSTRUCTION  
2024-MAR-01

VFPA DRAWING NUMBER:  
332-004-UT-###

Ref. No.	REFERENCE



No.	Date	REVISION	Dr'n	Ch'd
C	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.
B	2024-MAR-01	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.
A	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.




DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	H 1:500 V: 1:50
VFPA SITE	332-004

WCD MARINE YARD BUILD-OUT  
COQUITLAM, BC  
STORM PLAN AND PROFILE  
SHEET 3 OF 3

SIZE	DWG.	SHEET	REV.
D	105716-S00-KIE-DAU-DWG-4107	3 OF 3	C





DATE: 2024/03/17 - 8:35pm  
PATH: C:\Users\ShunP.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4108.dwg



SECTION S  
Scale: N.T.S.


NE SAFETY CHANNEL

FRASER RIVER




SECTION T  
Scale: N.T.S.

**PRELIMINARY**  
**NOT FOR CONSTRUCTION**  
2023-NOV-14



ALIGNMENT: Trestle West



ALIGNMENT: Trestle East

STORM TYPE, SIZE LENGTH AND GRADE	PROP. 14.63m OF 200mmØ CPVC @ 0.5%	PROP. 11.56m OF 200mmØ CPVC @ 0.5%	PROP. 7.09m OF 200mmØ CPVC @ 0.5%	PROP. 13.24m OF 200mmØ CPVC @ 0.5%	PROP. 13.24m OF 200mmØ CPVC @ 0.5%	PROP. 13.20m OF 200mmØ CPVC @ 0.5%	PROP. 7.55m OF 200mmØ CPVC @ 0.5%
STORM SEWER INVERT ELEVATIONS	6.59m(E)	6.50m(W) 6.50m(E)	6.45m(W) 6.45m(N)	6.41m(S) 6.41m(N)	6.34m(S) 6.34m(N)	6.28m(S) 6.28m(N)	6.21m(S) 6.21m(N)
GROUND ELEVATION	-1.33	-0.63		0.11		1.37	2.71 2.84
CHAINAGE	50+000	50+016.19	50+025	50+030.82	50+042.38	50+049.48	50+052.72

STORM TYPE, SIZE LENGTH AND GRADE	PROP. 14.63m OF 200mmØ CPVC @ 0.5%	PROP. 13.24m OF 200mmØ CPVC @ 0.5%	PROP. 13.24m OF 200mmØ CPVC @ 0.5%	PROP. 13.24m OF 200mmØ CPVC @ 0.5%	PROP. 13.20m OF 200mmØ CPVC @ 0.5%	PROP. 13.20m OF 200mmØ CPVC @ 0.5%	PROP. 13.20m OF 200mmØ CPVC @ 0.5%	PROP. 17.78m OF 250mmØ C76 CL IV CONC @ 5.8%
STORM SEWER INVERT ELEVATIONS	6.59m(E)	6.50m(W) 6.50m(E)	6.45m(W) 6.45m(E)	6.39m(W) 6.39m(N)	6.28m(S) 6.28m(N)	6.21m(S) 6.21m(N)	6.14m(S) 6.14m(N)	6.01m(S) 6.01m(N)
GROUND ELEVATION	-1.57	-1.74	-1.48	-0.85	0.79	2.55	6.04 6.02	6.04 6.02
CHAINAGE	51+000	51+016.19	51+025	51+030.82	51+045.45	51+050	51+053.86	51+075



DESIGN BY B.Y.  
DRAWN BY T.W.  
APPROVED K.B.  
DATE 2024-MAR-01  
SCALE H 1:500 V: 1:50  
VFPA SITE 332-004

**WCD MARINE YARD BUILD-OUT**  
**COQUITLAM, BC**  
**TRESTLE DRAINAGE PLAN AND PROFILE**

105716-S00-KIE-DAU-DWG-4108

SHEET 1 OF 1  
REV. C

VFPA DRAWING NUMBER:  
332-004-UT-###




Ref. No. REFERENCE

No. Date REVISION Dr'n Ch'd

C	2024-MAR-29	ISSUED FOR VFP PER	T.W.	B.Y.
B	2024-MAR-01	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.
A	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.



DATE: 2024/03/17 - 8:28pm  
PATH: C:\Users\ShunPa.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4109.dwg



STORM TYPE, SIZE LENGTH AND GRADE	PROP. 7.19m OF 200mmØ C76 CLASS III CONC @ 0.5%		PROP. 40.00m OF 200mmØ CPVC @ 0.5%		PROP. 7.24m OF 200mmØ C76 CLASS III CONC @ 0.5%	
STORM SEWER INVERT ELEVATIONS	5.20m(N)		5.00m(S) 5.00m(W)		4.96m(E) 4.94m(SW) 4.90m(NE)	
GROUND ELEVATION	-1.21 -1.21		-0.84 -0.84		7.20 7.20	
CHAINAGE	52+975 53+000		53+025 53+028.02		53+050 53+068.02 53+075.21 53+082.45	

PRELIMINARY  
NOT FOR CONSTRUCTION  
2024-MAR-01

VFPA DRAWING NUMBER:  
332-004-UT-###

Ref. No.	REFERENCE



No.	Date	REVISION	Dr'n	Ch'd
C	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.
B	2024-MAR-01	ISSUED FOR DFO FISHERIES ACT AUTHORIZATION REVIEW	T.W.	B.Y.
A	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.





DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	H 1:500 V: 1:50
VFPA SITE	332-004

WCD MARINE YARD BUILD-OUT  
COQUITLAM, BC  
RORO RAMP DRAINAGE PLAN AND PROFILE

SIZE	DWG.	105716-S00-KIE-DAU-DWG-4109	SHEET	REV.
D			1 OF 1	C



DATE: 2024/03/21 - 2:39pm  
PATH: C:\Users\ShunP.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4110.dwg



ALIGNMENT: MY STM 6

STORM TYPE, SIZE LENGTH AND GRADE	PROP. 28.34m OF 375mmØ SDR35 PVC @ 1.8%		PROP. 39.03m OF 375mmØ SDR35 PVC @ 0.6%	
STORM SEWER INVERT ELEVATIONS	5.17m(E) 4.67m(W)		4.67m(E) 4.43m(W) 4.43m(S)	
GROUND ELEVATION				
CHAINAGE	14+975	15+000	15+008.67	15+125

**PRELIMINARY**  
NOT FOR CONSTRUCTION  
2024-MAR-01

VFPA DRAWING NUMBER:  
332-004-UT-###

Ref. No.	REFERENCE



A	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.	
No.	Date	REVISION	Dr'n	Ch'd	





DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	H 1:500 V: 1:50
VFPA SITE	332-004

**WCD MARINE YARD BUILD-OUT**  
**COQUITLAM, BC**  
**TRUCK SCALE DRAINAGE PLAN AND PROFILE**

SIZE	DWG.	SHEET	REV.
D	105716-S00-KIE-DAU-DWG-4110	1 OF 1	A



DATE: 2024/03/17 - 8:19pm  
PATH: C:\Users\ShunPa.Wang\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4201.dwg



PRELIMINARY  
NOT FOR CONSTRUCTION  
2023-NOV-14

VFPA DRAWING NUMBER:  
332-004-UT-4201



DESIGN BY B.Y.  
DRAWN BY T.W.  
APPROVED K.B.  
DATE 2024-MAR-29  
SCALE H 1:500 V: 1:50  
VFPA SITE 332-004

WCD MARINE YARD BUILD-OUT  
COQUITLAM, BC  
WATERLINE PLAN AND PROFILE  
SHEET 1 OF 3





Ref. No. REFERENCE

B	2024-MAR-29	ISSUED FOR VFPA PER	T.W.	B.Y.
A	2023-NOV-14	ISSUED FOR 90%	T.W.	B.Y.
No.	Date	REVISION	Dr'n	Ch'd

ENGINEERING DEPARTMENT

SIZE DWG. 105716-S00-KIE-DAU-DWG-4201 SHEET 1 OF 3 REV. B

DATE: 2024/03/17 - 8:21pm  
PATH: C:\Users\ShunPa.Wang\OneDrive\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4202.dwg



ALIGNMENT: MY WAT 2



ALIGNMENT: MY WAT 4

WATER TYPE, SIZE LENGTH AND GRADE	PROP. 9.78m OF 50mmØ PEX (WHITE) @ 0.8%		PROP. 16.50m OF 50mmØ PEX (WHITE) @ 7.2%		PROP. 24.94m OF 50mmØ PEX (WHITE) @ 0.0%		PROP. 44.48m OF 50mmØ PEX (WHITE) @ 0.0%	
	4.98 (N)	4.98 (W)	4.98 (S)	5.06 (N)	6.25 (E)	6.79 (S)	6.79 (S)	6.79 (N)
WATER SEWER INVERT ELEVATIONS	4.98 (W)	4.98 (S)	5.06 (N)	5.06 (W)	6.25 (E)	6.79 (S)	6.79 (S)	6.79 (N)
GROUND ELEVATION				3.42	3.42		2.71	2.71
CHAINAGE	22+150	22+125	22+114.26	22+104.47	22+100	22+097.97	22+075	22+063.03

WATER TYPE, SIZE LENGTH AND GRADE	PROP. 4.08m OF 50mmØ PEX (WHITE) @ 1.5%		PROP. 7.82m OF 50mmØ PEX (WHITE) @ 2.1%		PROP. 3.08m OF 50mmØ PEX (WHITE) @ 0.4%	
	3.08 (E)	3.08 (W)	3.08 (S)	2.91 (N)	2.85 (N)	2.84 (N)
WATER SEWER INVERT ELEVATIONS	3.08 (E)	3.08 (W)	3.08 (S)	2.91 (N)	2.85 (N)	2.84 (N)
GROUND ELEVATION			4.16			-0.20
CHAINAGE	24+075	24+050	24+024.05	24+016.57	24+012.50	24+009.42


PRELIMINARY  
NOT FOR CONSTRUCTION  
2023-NOV-14

VFPA DRAWING NUMBER:  
332-004-UT-###

									 <div>PORT of vancouver</div> <div>Vancouver Fraser Port Authority</div>									<div>DESIGN BY B.Y.</div>	<div>DRAWN BY T.W.</div>	<div>APPROVED K.B.</div>	<div>DATE 2024-MAR-29</div>	<div>SCALE H 1:500 V: 1:50</div>	<div>VFPA SITE 332-004</div>	<div>WCD MARINE YARD BUILD-OUT COQUITLAM, BC WATERLINE PLAN AND PROFILE SHEET 2 of 3</div>																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																



DATE: 2024/03/17 - 8:29pm  
PATH: C:\Users\ShunPa.Wang\OneDrive\Documents\Kiewit\WCD Marine Yard\Project Files\40 Design Eng\30 CIV\CAD\Sheets\105716-S00-KIE-DAU-DWG-4203.dwg



PRELIMINARY  
NOT FOR CONSTRUCTION  
2023-NOV-14

VFPA DRAWING NUMBER:  
332-004-UT-4203

Ref. No.	REFERENCE






B	2024-MAR-29	ISSUED FOR VFPA PER		T.W.	B.Y.
A	2023-NOV-14	ISSUED FOR 90%		T.W.	B.Y.
No.	Date	REVISION	Dr'n	Ch'd	

**PORT of  
vancouver**

Vancouver Fraser  
Port Authority

ENGINEERING DEPARTMENT

DESIGN BY	B.Y.
DRAWN BY	T.W.
APPROVED	K.B.
DATE	2024-MAR-29
SCALE	H 1:500 V: 1:50
VFPA SITE	332-004

WCD MARINE YARD BUILD-OUT COQUITLAM, BC WATERLINE PLAN AND PROFILE SHEET 3 OF 3			
SIZE	DWG.	105716-S00-KIE-DAU-DWG-4203	REV.
3 OF 3			B